

Desktop Card Embosser

By NBS Technologies

Advantage™ 2000 M2® / M3® Embossers

Flexibility you need and the quality you can trust

The Advantage 2000 series is our tabletop card embosser line with a reputation that stands on its own. The Advantage M2 and M3 can be configured to include any or all of the following features: Magnetic Stripe Encoding, Thermal Printing, Contact Smart Card, Embossing, Rear Indent, Front Indent and Color Tipping of Embossed characters. These machines have been designed with flexibility in mind. Card personalization features can be added and removed in the field as your personalization needs change.



The M2 and M3 embossers can be operated either online from a host system using its internal formats or connected directly to a PC using the NBS Smartsys™ Tabletop software. SmartSys software is a powerful Windows® based card design and production package. Smartsys was developed by NBS and features a graphical interface for easy card design and job setup. The software is not only used for card layout, but also handles input data from a database or data file as well as formatting of card fields such as encoding, images, text, etc.

THE ADVANTAGE™ 2000 M2 / M3 EMOSSERS OFFERS THESE KEY FEATURES AND BENEFITS:



DESKTOP FLEXIBILITY

- 110 character embossing wheel
- Indent printing front or rear
- Field upgradable



NETWORK AND ENCODING

- Magnetic stripe encoding
- Contact smart card personalization
- 300 dpi thermal printing



EASY-TO-USE

- Auto feed input hopper (200 card capability)
- Modular design
- Auto unload stacker
- Color tipper

Embosser Specifications

Embossing method	110 characters wheel embosser Color tipping (optional) Indent printing front or rear (optional)
Card encoding options	Magnetic encoding - ISO or JIS ISO 7816 smart card personalization [EMV compliant] (optional)
Embossing speed	M2 - up to 280 cards per hour (depending on configuration) M3 - up to 350 cards per hour
Embosser interfaces	Operator panel : LCD display, 2-lines, 40 characters Communication: RS232
Embossing characteristics	CR80 Max. lines: 11, Max. simplex characters per line: 31, Max. OCR characters per line: 22, Maximum Blocco characters per line: 22 Thermal Print Area: (CR80 card size only) 1.750" x 3.125" (5.468 sq inches) Printing cannot be placed less than 100" from the top edge of card, .350" from bottom edge of card, and .200" from left and right edges of the card
Card capacity	200 cards input hopper, automatic feeding 200 finished cards output hopper (full sensor hopper) Single card front input feeder
Weight	130 lbs (59kg)
Power source	110V, 50-60 Hz, 4 amp 220V, 50-60 Hz, 3 amp
Dimensions	18.75" (476mm) D x 28.63" (727mm) W x 16.5" (419mm) H
Environment	Operating temperature: 14 - 27 °C / 58 - 80 °F, Relative humidity: 20% to 85% non-condensing

Card Specifications

Types	Card size: CR80 - 3.375" x 2.125" (35.7mm x 54mm) Card thickness: .020" to .030" (.5mm to .8mm) Card material: Polyvinylchloride (PVC)
--------------	--

UPGRADE TO SMARTSYS TABLETOP MACHINE CONTROL SOFTWARE AND GET MORE FEATURES



SMARTSYS™

Upgrade to SmartSys tabletop machine control software and get more features. For even more enhanced capabilities, consider upgrading your Advantage embosser's to SmartSys tabletop, the user-friendly, feature-packed batch issuance software.



EMV BRANCH ISSUANCE SOFTWARE

Couple your Advantage M2000 series embosser with Xpressi™ software for an EMV branch card issuance solution that is cost effective and easy to implement. Supporting multiple EMV configurations, chip types and even printer brands with one system, this solution gives an issuer the flexibility to keep their future expansion and operation options open for change.



w: www.nbstech.com
e: info@nbstech.com

Contact our NBS card personalization experts for full details on this and other card personalization products at:

Global Headquarters
10925 Bren Road E
Minneapolis, MN 55343
USA
tel: +1 952.912.9400
fax: +1 952.912.9439
email: info@nbstech.com

B1 Moorfield Point
Slyfield Industrial Park
Guildford, Surrey GU1 1RU
United Kingdom
tel: +44 (0)1483 563200
fax: +44 (0)1483 511189
email: javelin@nbstech.com

20614 Eastleigh Crescent
Langley BC V3A 4C4
Canada
tel: +1 604.530.6012
fax: +1 604.530.9685
email: info@nbstech.com