



P205

VALUE



P205 Card Printer

Key Features

- » 4 Seconds/Card Print Speed
- » Convenient Front Card Loading and Output
- » Monochrome Single-Sided Card Printing
- » USB/Parallel or USB/Serial Interfaces
- » 50 Card Capacity Feeder

Card Printing Is Easier Than Ever

The Zebra P205 is an economical, single-sided monochrome card printer with convenient, easy-to-use features to produce personalized cards on-demand with text, or bar codes for lower volume applications.

Use the P205 card printer to print:

- » Visitor badges
- » Loyalty cards
- » Personalized Gift and Membership cards

Zebra P205 Advantages

Operator Convenience: Patented openACCESS® clam-shell design, easy-to-use "load and go" ribbon cartridge system, quick reference Pocket Guide, Windows® 98, ME, NT, 2000 and XP printer drivers with install wizard.

Economical Operation: Low cost printer for low-volume applications.



**Card
Printer
Solutions**

P205

Card Printer Product Specifications



General Specifications

- » High speed card printing
- » 2MB image memory standard
- » Windows[®] drivers for 98, ME, NT, 2000 and XP
- » Patented openACCESS[®] clamshell design
- » Front card loading and output
- » Multi-Function Button with LED indicator ring
- » Two year warranty
- » Two year (unlimited passes) printhead warranty

Printing

- » Monochrome thermal transfer printing
- » 4 seconds/card monochrome
- » 300 dpi (11.8 dots/mm) print resolution

Bar Codes

- » Code 39, Code 128 B & C with & without check digit
- » 2 of 5 & 2 of 5 Interleaved
- » UPC-A, EAN 8 & EAN 13
- » PDF-417 2D bar code and other symbologies can be printed via Windows drivers

Fonts

- » True Type fonts via Windows driver

Card Specifications

- » Types: PVC, PVC Composite
- » Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- » Magnetic Stripe-ISO 7811
- » Card thickness: 30 mil (.76mm)
- » Card feeder capacity: 50 cards (30 mil)
- » Card output hopper capacity: 20 cards (30 mil)

Ribbon Specifications*

- » Monochrome: 500 cards/roll
- *for optimum printer performance
use Genuine Zebra Supplies*



Communications Interface

- » USB and Centronics Parallel
- » USB and RS232 Serial

Mechanical *(includes card feeder)*

- » Width: 7.16 in (182 mm)
- » Depth: 11.9 in (303 mm)
- » Height: 7.1 in (180 mm)
- » Weight: 6.4 lbs (2.9 kg)

Electrical

- » 110 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- » FCC Class A, CE, UL and CUL approved

Environmental

- » Operating Temperature: 60°F to 86°F (15°C to 30°C)
- » Operating Humidity: 20% to 65% non-condensing
- » Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- » Storage Humidity: 20% to 70% non-condensing
- » Ventilation: Free air

Options

- » Magnetic encoder, tracks 1 & 2
- » Cleaning supplies
- » Service manual

www.zebracard.com



An ISO 9001 registered company ©2004 ZIH Corp.
Specifications listed are for base model printers with standard features only unless otherwise notes. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof.
Part No. P205-08/05



Advanced Card Systems and Solutions, Inc.

1775 Route 34 South, Suite D12
Farmingdale, NJ 07727
Tel: (732) 282-9002
Fax: (732) 282-9003

Web: www.AdvancedCardSystems.com
Email: Sales@AdvancedCardSystems.com