



P310i

PERFORMANCE



Single-Sided Color Printer Optimized for Fast Color Printing

The Zebra P310i is an easy to use, reliable, single-sided card printer has convenient features to produce superior quality card printing at an affordable price.

Use the P310i card printer for:

- » Employee ID Cards
- » Time and Attendance Cards
- » Student ID's and Facilities Access Control Cards
- » Club Membership and Loyalty Cards

Zebra P310i Advantages

Advanced Color Printing: Enhanced color-processing firmware and new richer color formulation

Reliable Operation: Based on the highly reliable, field-proven P310 print engine

i Series Intelligent Printing System: Enhanced i Series functionality makes high image quality card printing a simple function for all users. The system features:

- » Advanced RFID Technology
- » Automatic Driver Configuration
- » Intelligent Color Optimization
- » Ribbon Image Counter & Ribbon Low Notification
- » Enhanced Ribbon Formulation

P310i Card Printer

Key Features

- » 25 Seconds/Card Print Speed
- » Full Color Single-Sided Card Printing
- » Parallel or USB Interface
- » 75 Card Capacity Feeder
- » i Series Printers require the use of TrueColours™ i Series ribbons for full color printing

*i*series



**Card
Printer
Solutions**

P310i

Card Printer Product Specifications



General Specifications

- » High speed printing
- » 144 cards/hour for color, single sided (YMCKO)
- » 900 cards/hour for resin black (K)
- » 2MB image memory standard
- » Windows® drivers for 98, ME, NT, 2000 and XP
- » Bi-directional driver communication
- » One year printer warranty
- » One year (unlimited passes) printhead warranty

Color Printing

- » Color dye sublimation or monochrome thermal transfer printing
- » 25 seconds per card full color single sided (YMCKO)
- » 300 dpi (11.8 dots/mm) print resolution

Bar Codes

- » Code 39, Code 128 B & C with & without check digit
- » 2 of 5 & 2 of 5 Interleaved
- » UPC-A, EAN 8 & EAN 13
- » PDF-417 2D bar code and other symbologies can be printed via Windows drivers

Fonts

- » Arial and Arial Bold
- » True Type fonts via Windows driver

Card Specifications

- » Types: PVC, PVC Composite
- » Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- » Magnetic Stripe-ISO 7811
- » Smart Card-ISO 7816-2
- » Card thickness: 10 mil (.25mm) to 60 mil (1.524mm)
- » Card feeder capacity: 75 cards (30 mil)
- » Card output hopper capacity: 75 cards (30 mil)

Ribbon Specifications*

- » i Series Printers require the use of i Series ribbons for full color printing
- » Monochrome: 1500 & 1000 cards/roll
- » Monochrome colors: black, red, blue, green, silver, gold, white and scratch-off gray
- » YMCKO: 200 & 330 cards/roll
- » KdO: 500 cards/roll
- » KrO: 500 cards/roll
- » Overlay varnishes: Clear and Hologram: 350 cards/roll



**for optimum printer performance use Genuine Zebra Supplies*

Communications Interface

- » USB with Centronics Parallel (parallel cable included)

Mechanical

- » Width: 12.4 in (315 mm)
- » Depth: 7.75 in (198 mm)
- » Height: 8.7 in (220 mm)
- » Weight: 13.4 lbs (6.1 kg)

Electrical

- » 110 ~ 230 Volts AC, 50 ~ 60 Hz (auto switching)
- » FCC Class B, CE, UL and CUL approved

Environmental

- » Operating Temperature: 60°F to 86°F (15°C to 30°C)
- » Operating Humidity: 20% to 65% non-condensing
- » Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- » Storage Humidity: 20% to 70% non-condensing
- » Ventilation: Free air

Options

- » Smart card contact station (30 mil cards only)
- » Magnetic encoder (30 mil cards only)
- » Cleaning supplies
- » Service manual

www.zebracard.com



Zebra Technologies Corporation



An ISO 9001 registered company ©2003 ZIH Corp.
Specifications listed are for base model printers with standard features only unless otherwise notes. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof. **Part No. P310I-08/05**



Advanced Card Systems and Solutions, Inc.

1775 Route 34 South, Suite D12
Farmingdale, NJ 07727

Tel: (732) 282-9002

Fax: (732) 282-9003

Web: www.AdvancedCardSystems.com

Email: Sales@AdvancedCardSystems.com