



P420i

PERFORMANCE



P420i Card Printer

Key Features

- » 35 Seconds/Card Print Speed (YMCKOK)
- » Two-line LCD display with printer status and user commands
- » Full metal enclosure with viewing window
- » Full Color or Monochrome Dual-Sided Card Printing
- » USB with Parallel or USB with Built-in Ethernet
- » 100 Card Capacity Feeder
- » *i* Series Printers require the use of TrueColors™ *i* Series ribbons for full color printing

*i*series

Reliable Performance for On-Demand Card Printing

Solve your on-demand card printing needs with Zebra's P420i. With its LCD display and convenient user features, this rugged, dual-sided card printer readily prints high quality, personalized photo ID cards for high volume applications.

Use the P420i card printer for:

- » Event Badges
- » Theme Park Season Passes
- » Student IDs and Access Control Cards
- » Fishing and Gaming Licenses

Zebra P420i Advantages

Advanced Color Printing: Enhanced color-processing firmware and new richer color formulation

Reliable Operation: Full metal enclosure and field-proven reliable P310 print engine. Reject hopper separates cards that fail encoding prior to printing

***i* Series Intelligent Printing System:** Enhanced *i* Series functionality makes high image quality card printing a simple function for all users. The system features:

- » Advanced RFID Technology
- » Automatic Driver Configuration
- » Intelligent Color Optimization
- » Ribbon Image Counter & Ribbon Low Notification
- » Enhanced Ribbon Formulation



**Card
Printer
Solutions**

P420i

Card Printer Product Specifications



General Specifications

- » High speed printing
- » 102 cards/hour full color, dual-sided (YMCKOK)
- » 4MB image memory standard
- » Standard card flip over feature for dual-sided printing
- » Windows® drivers for 98, NT, 2000, ME, XP
- » Bi-directional driver communication
- » One year printer warranty
- » One year (unlimited passes) printhead warranty
- » Pass-code electronic lock

Color Printing

- » Color dye sublimation or monochrome thermal transfer printing
- » 35 seconds per card full color dual-sided (YMCKO/K)
- » 300 dpi (11.8 dots/mm) print resolution

Bar Codes

- » Code 39, Code 128 B & C with & without check digit
- » 2 of 5 & 2 of 5 Interleaved
- » UPC-A, EAN 8 & EAN 13
- » PDF-417 2D bar code and other symbologies can be printed via Windows drivers

Fonts

- » Arial and Arial Bold
- » True Type fonts via Windows driver

Card Specifications

- » Types: PVC, PVC Composite
- » Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- » Magnetic Stripe-ISO 7811
- » Smart Card-ISO 7816-2
- » Card thickness: 30 mil (.76mm) to 60 mil (1.524mm)
- » Card feeder capacity: 100 cards (30 mil)
- » Card output hopper capacity: 100 cards (30 mil)

Electrical

- » 110 ~ 230 Volts AC, 50 ~ 60 Hz (auto switching)
- » FCC Class B, CE, UL and CUL approved

Ribbon Specifications*

- » i Series Printers require the use of i Series ribbons for full color printing
- » Monochrome: 1500 & 1000 cards/roll
- » Monochrome colors: black, red, blue, green, silver, gold white & scratch-off grey
- » KdO: 500 cards/roll
- » KrO: 500 cards/roll
- » YMCKOK: 170 cards/roll
- » YMCKO: 200 & 330 cards/roll
- » Overlay varnishes: thermal transfer, clear and holographic overlays available



**for optimum printer performance use Genuine Zebra Supplies*

Communications Interface

- » USB with Centronics Parallel (parallel cable included)
- » Built-in Ethernet Option

Mechanical

- » Width: 20.90 in (523 mm)
- » Depth: 10.17 in (253 mm)
- » Height: 10.76 in (269 mm)
- » Weight: 27.5 lbs (12.5 kg)

Environmental

- » Operating Temperature: 60°F to 86°F (15°C to 30°C)
- » Operating Humidity: 20% to 65% non-condensing
- » Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- » Storage Humidity: 20% to 70% non-condensing
- » Ventilation: Free air

Options

- » Built-in Ethernet
- » Smart card contact station (30 mil cards only)
- » Magnetic encoder (30 mil cards only)
- » Cleaning supplies
- » Service manual

www.zebracard.com



Zebra Technologies Corporation



An ISO 9001 registered company ©2005 ZIH Corp. Specifications listed are for base model printers with standard features only unless otherwise notes. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof. **Part No. P420i-08/05**



Advanced Card Systems and Solutions, Inc.

1775 Route 34 South, Suite D12
Farmingdale, NJ 07727
Tel: (732) 282-9002
Fax: (732) 282-9003

Web: www.AdvancedCardSystems.com
Email: Sales@AdvancedCardSystems.com