



# P640i

## SECURITY



# P640i Card Printer

### Key Features

- » Full Color Dual-Sided Card Printing and Dual-Sided Lamination
- » Micro Card Positioning for Excellent Color Registration and Superior Print Quality
- » High capacity waste free laminate 600 cards/roll
- » Numerous Security Features (covert printing, Secure ID/Key, ID/Log)
- » Built-in Ethernet for Network Capability (optional)

*i*series

### A Complete Security Solution for Tamper Resistant ID Cards

Adding unique security features to ID cards is easier, faster, more economical with Zebra's P640i. This next generation printer from Zebra delivers mission-critical reliability and superior affordability. Protect your ID cards from counterfeiting, alteration or duplication with the P640i's customizable levels of security. Zebra is one of the first manufacturers to offer an extended range of security options for all printing components - cards, ribbons, laminates and printers. When security counts, count on Zebra.

Use the P640i printer for:

- » Agency Licenses
- » High Security Access Control ID Cards
- » Law Enforcement and Correctional Facility ID Cards
- » Airport ID Cards
- » Any card application requiring long lasting, secure issuance of tamper-resistant ID's

### Many "Best In Class" features:

- » Lowest consumables cost per card in the industry
- » Highest production output speed with continuous card loading feature
- » Superior print quality for optimal color fidelity and precision details
- » Reliable and easy to use



**Card  
Printer  
Solutions**

# P640i

## Card Printer Product Specifications



### General Specifications

- » Dual-sided printing and one-pass waste-free dual-sided lamination
- » 120 cards/hour dual-sided printing and laminating (YMCK ribbon & 1.0 mil laminate both sides)
- » Micro-positioning card transport system for enhanced color photos
- » Complete system security features & options for printer, ribbons, laminate, cards, and card issuance process
- » Covert printing capability text approx 17 mil high
- » Automated card cleaning before printing
- » Built-in Ethernet option for networking capability
- » Windows® drivers for 2000 and XP with advanced security features (ID/Log & password protection)
- » One year printer warranty
- » One year (unlimited passes) printhead warranty

### Color Printing

- » Color dye sublimation and resin K
- » 30 seconds per card (YMCK & dual sided lamination)
- » 300 dpi (11.8 dots/mm) print resolution

### Bar Codes

- » Bar codes and other symbologies available via Windows driver

### Fonts

- » True Type or other type fonts via Windows driver

### Card Specifications

- » Types: PVC Composite
- » Card width/length: ISO CR-80 - ISO 7810 2.12" (54mm) x 3.38" (86mm)
- » HiCo Magnetic Stripe - ISO 7811
- » Contact Smart Card - ISO 7816 Compliant
- » Contactless Smart Card - Mifare® or HID iClass™
- » Card thickness: 27 mil - 39 mil
- » Card input hopper capacity: 150 cards

### Ribbon Specifications\*

- » YMCK: 600 cards/roll
- » YMCKK: 500 cards/roll
- » YMCUVK: 500 cards/roll
- » Cleaning cartridge: cleans 3,000+ cards

*\*for optimum printer performance use Genuine Zebra Supplies*



### Laminate Specifications\*\*

- » Linerless & wastefree 1.0 mil laminate, 600 cards/roll
- » 2 Laminate cassettes (upper & lower)
- » Laminates available:
  - » Clear full size, clear for magnetic stripe cards and clear for smart cards. Custom laminates available upon request:
    - » Holographic images
    - » Special OVD images
    - » UV images

*\*\*for optimum laminator performance use Genuine Zebra Supplies.*

### Communications Interface

- » USB 1.1 (Standard)
- » Factory Installed Options
  - » Built-In Ethernet
  - » Bi-directional Parallel with ECP support

### Mechanical

- » Width: 27.5 in (699 mm) not including exit hopper
- » Depth: 9.7 in (246 mm)
- » Height: 11.5 in (292 mm)
- » Weight: 35 lbs (15.9 kg)

### Electrical

- » 110 - 220 Volts AC, 50/60 Hz
- » FCC Class A, UL, CUL, & CE approved

### Environmental

- » Operating temperature: 50°F to 95°F (10°C to 35°C)
- » Operation humidity: 20% to 80% non-condensing
- » Storage temperature: -4°F to 158°F (-20°C to 70°C)
- » Storage humidity: 5% to 90% non-condensing
- » Ventilation: Free air

### Options

- » ID/Key security printing feature
- » Magnetic Encoder
- » Smart Card Contact Station
- » Smart Card Contactless encoder/reader
- » Smart Card Contact encoder/reader
- » Warranty programs

[www.zebracard.com](http://www.zebracard.com)



Zebra Technologies Corporation



An ISO 9001 registered company ©2005 ZIH Corp.  
Specifications listed are for base model printers with standard features only unless otherwise notes. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof. **Part No. P640i-08/05**



Advanced Card Systems and Solutions, Inc.

1775 Route 34 South, Suite D12  
Farmingdale, NJ 07727

Tel: (732) 282-9002  
Fax: (732) 282-9003

Web: [www.AdvancedCardSystems.com](http://www.AdvancedCardSystems.com)  
Email: [Sales@AdvancedCardSystems.com](mailto:Sales@AdvancedCardSystems.com)