Desktop Card Embosser

nbs TECHNOLOGIES EMBOSSER

By NBS Technologies

Advantage™ M20

The Advantage M20 is the latest in the NBS Advantage embosser family of products. Secure, reliable and affordable, the Advantage M20 has been designed specifically for the instant personalization and issuance of EMV compliant debit and/or credit cards.

The Advantage M20 possesses a stainless steel 120-character daisy wheel for embossing, together with simultaneous front and rear indenting. A full range of international characters is available which makes this a truly universal embosser.





The Advantage M20 is provided with either a standard Windows driver for seamless integration with existing card personalization and issuing applications, or with a specific software library to allow its many features to be included in custom applications and solutions. We can also supply XpressiTM, NBS's distributed issuance solution designed especially for financial institutions wanting to issue cards at branch level.

THE DESKTOP EMBOSSER AND ENCODER DESIGNED FOR THE SECURE AND RELIABLE INSTANT PERSONALIZATION AND ISSUANCE OF CREDIT AND DEBIT CARDS

THE ADVANTAGE™ M20 OFFERS THESE KEY FEATURES AND BENEFITS:



DESKTOP FLEXIBILITY

- 120 character embossing wheel
- Dual (front & rear) indent available
- Anchors for bolting down the embosser to its operating station



NETWORK AND ENCODING

- High/low coercivity magnetic stripe encoding
- Contact and contactless smart card personalization
- Triple DES encryption
- Contact, Contactless or both



EASY-TO-USE

- 100-card hopper for automatic card feeding
- Single card front input feeder
- Access cover secured with electronic lock under software control

CONSULTING

SOFTWARE

HARDWARE

SMART CARD MANUFACTURING



Embosser Specifications

Embossing method	120 characters stainless steel daisy wheel embosser, easy installation of new types
	Rear indenting, easy cartridge replacement
	Tipping
	Front indent (optional)
Card encoding options	Magnetic stripe encoder, high/low coercivity
	ISO 7816 smart card personalization [EMV compliant] (optional)
	ISO 14443 contactless card personalization (optional)
	Triple DES encryption
Embossing speed	1 card in 30 seconds (excluding chip personalization)
Embosser interfaces	Operator panel : 2x24 LCD display, 12 keys numeric keypad, 5 status LEDs
	Communication: RS232, Ethernet, USB 2.0
Software drivers	DLL for Windows 2000/XP/Vista/W7 drivers available
Embossing characteristics	OCR 7B, Standard Gothic
	Rear Indent: OCR B1
	Front Indent: OCR B4, OCR B1
	A full range of other emboss/indent characters and fonts is available
Card capacity	100 cards input hopper, automatic feeding
	50 finished cards output hopper, hopper full sensor
	30 cards reject bin, bin full sensor
	Single card front input feeder
Weight	86 lbs (39kg)
Power source	110-230 Volts, 50-60 Hz, 200W
	CE, CSA C & US, FCC Class A
	EN 60950
Dimensions	26.4" (670mm) D x 17.9" (455mm) W x 11.6" (295mm) H
Environment	Operating temperature: 10 - 40 °C / 50 -104 °F, Relative humidity: 20% to 80% non-condensing
	Storage temperature: 0 - 55 °C / 32 - 131 °F, Storage humidity: 5 - 95% non-condensing
	Transport: -15 - 55 °C / 5 - 131 °F, 5 - 95% RH (up to 20 hours)
Security	Mechanical and electronic software controlled locks

Card Specifications

Types CR80 – PVC – 0.76mm, 30 mil / ISO/IEC 7811, ISO/IEC7816



EMV INSTANT ISSUANCE SOFTWARE SOLUTION

Couple your Advantage M20 embosser with Xpressi™ software for an EMV branch card issuance solution that is cost effective and easy to implement. Supporting multiple EMV configurations, chip types and even printer brands with one system, this solution gives an issuer the flexibility to keep their future expansion and operation options open for change.





Corporate Headquarters Canada 703 Evans Avenue Toronto, Ontario M9C 5E9 Canada

tel: +1 416.621.1911 fax: +1 416.621.8875 Contact our NBS card personalization experts for full details on this and other card personalization products at:

Europe, Middle East, Africa B1 Moorfield Point Slyfield Industrial Park Guildford, Surrey GU1 1RU United Kingdom tel: +44 (0)1483 563200

tel: +44 (0)1483 563200 fax fax: +44 (0)1483 511189

North / South America 10925 Bren Road E Minneapolis, MN 55343 USA

tel: +1 416.840.8620 fax: +1 952.912.9439 Asia Pacific PO Box 780 Hurstville BC NSW 1481 Australia

tel: +61 (2) 9546 6841 fax: +61 (2) 9546 6851